



PLASMA CUTTING MACHINE (IGBT INVERTER BASED)



With the help of oil free compressed air delivery at 5.5kg/cm² & electricity cut all metals like Stainless Steel, MildSteel, Copper, Brass, Aluminum, Inconel, Monel, Titanium, Nickel, Chrome, Bronze, Galvanized Steel, Heated Steel, Wear Plates etc.

MODELS: Plasma 45i, Kali 45i, Kali 80i, Kali 100i, Kali 200i

FEATURES:

- Efficiency and Power factor over 90%.
- Saving over 50% compared to conventional machines.
- Air Cooled torch with 6meters long cable.
- Unique torch design which allows operator to place the torch on the job being cut.
- Safety interlocks for operators & machine against high/low voltage, low Airpressure etc.
- Design stakes care of EMI interference which is prominent with other machines.
- Post cutting operations such as grinding of dross etc. almost eliminated.
- Having facility of Gouging.

ONLYTWOCONSUMABALES

- ElectrodesandNozzle.
- WorksonGeneratorSupply.

STANDARDSCOPEOFSUPPLY:

- HeavyDutywatercooling&circulatingunitwith watertank,radiatorandcoolingfan.
- WatercooledAirPlasmaCuttingHandTorch ModelKH-200alongwith6 mtrs.ofcablehose assembly.
- Electrode&Nozzle&'O'Ringse t 5 sets.

OPTIONALACCESSORIES:

- Watercooledplasmacuttingtorchassembly of 6 meterssuitable for Mechanised operation.
- MotorisedtrolleyModel"CutMaster" suitableforstraightcuttingwith1.8 mtrslong rackandcirclecuttingattachment.

TECHNICAL SPECIFICATIONS

MODEL	KALI 80i
Input Supply	3Ph., 415Volts, 50Hz, Max. 40Amps
Max. OCV, Volts	400
Rated Output Current	20 - 60Amps., ±10%
Duty Cycle @ 60%	50 Amps.
Cutting Range, (Fine / Coarse)	25/32 mm
Cut Speed	10ipm for 25mm, 5ipm for 32mm
Max. Air Pressure	6 bar
Max. Air Flow Rate	220 L/min
Protection Class	IP 23
Insulation Class	"H"
Power Source Cooling	Forced Air
Reco. Torch Cooling	Air
Weight without Torch	40kgs. Approx.

AIR COOLED TORCHES

TORCHES





GOUGING SAMPLE

TORCHES SPARES



- A. Machine Torch Head
- B. Manual Torch Head
- 1. Front Cap for Machine Torch
- 2. Front Cap for Manual Torch
- 3. Nozzle
- 4. Nozzle Holder
- 5. Electrode Holder
- 6. Contact Tube
- 7. Electrode
- Torch head is quick connection type and same can be replaced within minutes without use of any tools/spanners.
- Torch has facility to adapt gouging torch to the same cable hose assembly.

STANDARD ACCESSORIES

- Plasma Hand Cutting Torch 6 mtrs. Long cables & hoses.
- Plasma Machine Cutting Torch 6 mtrs. Long cables & hoses for mechanized cutting.
- Circle cutting guide.
- Air Filtration kit, Water separator.

TECHNOCRATS PLASMA SYSTEMS PVT. LTD.



Regd. Office: - 310, Tapo Commercial Centre, Ram Mandir Road, Goregaon (West), Mumbai 400 104.

Tel: - 022 - 26763513 / 26763514 / 26764048.

Works: Nirav 2, Gaon Devi Indl. Complex, Sativali, Vasai (East), Dist. Thane - 401 208.

Tel: - 0250-2481511 / 2481512 / 2481513. Mobile: - 09320033114. E-mail: sales@technocratplasma.com • Website: www.technocratplasma.com